



# Specification Sheet

The **LOKi Cellular Gateway** is available in two models:

- **L-GW1** – Supports one connected controller (Ethernet)
- **L-GW2** – Supports two connected controllers

## FEATURES

- Secured Private Connection – Private Network and IP address
- Encrypted Private Network with Cellular Carrier – secured access and communications
- Device Certificate Authentication for maximum device security
- Compatible with most controllers and PLC's
- User programmable – Static IP and Port Forwarding
- Ships activated with annual cellular and data plan (data restrictions may apply)
- Portal Access includes access to all of your gateways with a single login
- Controller Network Programming not required – DHCP compatible
- WIFI Hotspot Included – access controller via wifi when on site
- Latency Monitoring – system monitors connection status for all of your gateways
- Dual antenna for best cellular connection
- Antenna extension kits available
- Two models – Supporting 1 or 2 connected controllers – single or dual Ethernet connections



## TECHNICAL SPECIFICATIONS

- Industrial construction
- *Environmental:* Water and Spray Proof
- *Power Supply:* 85-246 VAC / 47-440 hZ
- *Dimensions:* 7.5 x 8 x 2 inches
- *Operating Temperature:* -15C to 70C / -13F to 158 F 90% RH non-condensing
- FCC Part 15 Class A / ANSI C63.4.2014



ENERGY RESOURCE  
PRODUCTS

EnergyResourceProducts.com  
763-270-9334

